

## SMARTCODE™ 914 DEADBOLT FEATURING ZIGBEE® CONTROL4®

Model #: 914

Function: Single Cylinder Electronic Deadbolt



### Convenience

- 10 digit backlit keypad with one-touch locking
- Motorized locking mechanism enables true remote locking & unlocking
- Tapered deadbolt design permits misaligned doors to lock & unlock with ease
- SmartKey® easy re-key backup keyway
- Interior LED status indicator—Locked/unlocked status & low battery status
- Auto re-lock feature—locks door 30-seconds after unlocking

### Security

- 30 user access code capacity, 4-8 digit code length
- MasterCode feature
- 128-bit Advanced Encryption Standard (AES) communication
- Meets BHMA Grade 2 deadbolt operational and security standards
- Drill and pick resistant backup keyway with BumpGuard™ protection
- Incorrect code protection with audible alarm
- Audit trail logging stores access history in the lock memory
- Date/time scheduled user access control

### Customizable Features

- Auto re-lock 30-seconds after unlocking - ON/OFF
- Interior LED locked/unlocked status - ON/OFF
- Audible feedback - ON/OFF

### Specifications

#### Electrical:

**Input Power** 6V (4 x AA alkaline batteries)

#### Mechanical:

**Door Prep** 2 1/8" diameter face hole & 1" diameter latch hole

**Backset** Adjustable 2 3/8" or 2 3/4"

**Door Thickness** 1 3/8" - 2" automatic adjustment

**Faceplates** 1" x 2 1/4" round corner standard

**Strikes** Round corner strike 2 3/4" x 2 1/8"

**Latch** Round corner adjustable 2 3/8" x 2 3/4"

**Bolt** 1" throw, steel deadbolt

**Door Handing** Reversible

**Cylinder** SmartKey® Keyway

#### Environmental:

**Temperature Range** Exterior: -40°F to 150°F  
Interior: 32°F to 140°F

**Humidity** Exterior: 100% condensing  
Interior: 30% - 95% non-condensing


### Wireless Communication

- ZigBee® wireless technology
- RF Operation: 2.4 GHz (World) / 915 MHz (US)
- Range: Typical 250ft line of sight



### Electronic Compliance

- ZigBee: Control4, Crestron
- FCC Part 15



Design	A	B	C	D
Interior	2 3/4" (69.85 mm)	5 3/4" (146.05 mm)	2" (50.8 mm)	4 7/16" (112.71 mm)
Exterior	2 5/8" (66.68 mm)	4 7/16" (112.71 mm)	1 3/16" (30.163 mm)	---

### Command Classes

#### Lock Initiated Event Notifications:

- Lock secured using cylinder or inside turnpiece
- Lock un-secured using keyed cylinder or inside turnpiece
- Lock auto secured - Bolt jammed (not fully extended)
- Lock auto secured - Successful (fully extended)
- Lock un-secured by user (User-ID) at keypad
- Lock secured by user (User-ID) at keypad
- Lock secured by controller - Bolt jammed (not fully extended)
- Lock secured by controller - Successful (fully extended)
- Lock un-secured by controller - Successful (fully retracted)
- New user code (User-ID#) added to the lock
- All user codes deleted from lock
- Failed user code attempt at keypad
- Attempted access by user (User-ID#) outside of scheduled date/time
- Low battery level
- Critical battery level
- Battery level too low to operate deadbolt

**SMARTCODE 914**  
TOUCHPAD ELECTRONIC DEADBOLT

With ZigBee® Wireless Technology

