

Automotive Batteries											
BCI Group Size	Part Number	Volts	Cold Cranking Amps @ 0°F	Cranking Amps @ 32°F	Reserve Capacity Min @ 25A	Ah Capacity (20hr)	Length (in)	Width (in)	Height (in)	Battery Terminal Type	
MotoMaster Eliminator Ultra XD (High Performance AGM)											
78DT	10-7850	12	880	1050	133	60	10-7/8	7	7-3/4	A,S	
65	10-6550	12	930	1070	135	62	11-3/4	7-5/16	7-1/2	A	
MotoMaster Eliminator Ultra (AGM)											
24F	10-2420	12	710	850	120	60	10-3/16	6-3/4	8-5/8	A	
34	10-3420	12	770	925	120	60	10-3/16	7-1/16	7-7/8	A	
35	10-3520	12	650	780	110	53	9-1/16	6-5/8	8-5/8	A	
48/L3/H6	10-4820	12	720	865	120	70	10-7/8	6-7/8	7-1/2	A	
49/L5/H8	10-4920	12	850	1020	160	90	13-7/8	6-7/8	7-1/2	A	
51R	10-5120	12	440	530	75	45	9-5/16	4-15/16	8-5/8	A	
51	10-5121	12	440	530	75	45	9-5/16	4-15/16	8-5/8	A	
PRIUS	10-5122	12	440	530	75	45	9-5/16	4-15/16	8-1/2	JIS	
65	10-6520	12	750	910	140	70	12	7-3/16	7-1/2	A	
78	10-7820	12	770	925	120	60	10-3/16	7-1/16	7-1/8	S	
94R/L4/H7	10-9420	12	800	960	140	80	12-3/8	6-7/8	7-1/2	A	
MotoMaster Eliminator (Flooded)											
75DT	10-7580	12	690	825	100	58	9	6-15/16	8-1/8	A,S	
78DT	10-7880	12	770	950	120	70	10-3/16	6-15/16	8-1/8	A,S	
24F	10-2485	12	800	960	120	70	10-5/8	6-3/4	9-1/8	A	
24	10-2486	12	800	960	120	70	10-5/8	6-3/4	9-1/8	A	
26R	10-2685	12	550	660	85	49	8-11/16	6-13/16	7-11/16	A	
34	10-3485	12	800	960	120	70	10-3/16	6-13/16	8	A	
35	10-3585	12	585	700	100	58	9-7/16	6-7/8	8-15/16	A	
40R	10-4085	12	700	840	110	64	11	6-15/16	6-15/16	A	
47/L2/H5	10-4785	12	650	780	105	61	9-5/8	6-3/4	7-7/16	A	
48/L3/H6	10-4885	12	760	910	120	70	10-7/8	6-7/8	7-1/2	A	
49/L5/H8	10-4985	12	900	1080	185	107	14	6-7/8	7-7/16	A	
51R	10-5185	12	510	610	70	41	9-5/16	4-15/16	8-11/16	A	
51	10-5186	12	510	610	70	41	9-5/16	4-15/16	8-11/16	A	
65	10-6585	12	750	900	160	87	11-9/16	7-7/16	7-9/16	A	
75	10-7585	12	690	825	100	58	9-5/16	6-7/8	7-3/16	S	
86	10-8685	12	640	770	100	58	9	6-13/16	8	A	
94R/L4/H7	10-9485	12	790	950	140	81	12-7/16	6-15/16	7-1/2	A	
MotoMaster (Flooded)											
75DT	10-3570	12	630	785	100	58	9-7/16	6-15/16	8-1/8	A,S	
78DT	10-3478	12	800	960	120	70	10-3/16	6-15/16	8-1/8	A,S	
24F	10-2400	12	700	850	120	70	10-5/8	6-3/4	9-1/8	A	
24	10-2470	12	700	850	120	70	10-5/8	6-3/4	9-1/8	A	
25	10-2500	12	570	710	100	58	9-7/16	6-7/8	8-15/16	A	
26	10-2600	12	525	630	80	46	8-11/16	6-13/16	7-11/16	A	
26R	10-2673	12	540	635	80	46	8-11/16	6-13/16	7-11/16	A	
27F	10-2700	12	750	900	120	70	12-1/2	6-13/16	9	A	
27	10-2772	12	750	900	120	70	12-1/2	6-13/16	9	A	
34	10-3400	12	770	950	120	70	10-3/16	6-13/16	8	A	
35	10-3501	12	570	710	100	58	9-7/16	6-7/8	8-15/16	A	
36R	10-3672	12	650	800	95	55	10-1/4	7-3/16	7-15/16	A	
40R	10-4072	12	590	710	100	58	11	6-15/16	6-15/16	A	
41	10-4100	12	650	780	105	61	11-3/16	6-7/8	6-7/8	A	
42	10-4200	12	500	600	70	41	9-5/8	6-7/8	6-7/8	A	
MIATA	10-4672	12	320	415	45	26	7-3/4	5	6-7/8	A	
47	10-4700	12	600	750	85	49	9-5/8	6-3/4	7-7/16	A	
48	10-4800	12	690	825	110	64	11	6-3/4	7-7/16	A	
49	10-4900	12	850	1000	140	81	14	6-7/8	7-7/16	A	
51R	10-5100	12	450	525	70	41	9-5/16	4-15/16	8-11/16	A	
51	10-5101	12	450	525	70	41	9-5/16	4-15/16	8-11/16	A	
56	10-5672	12	580	700	90	52	10-7/16	6-5/16	8-3/8	A	
58	10-5858	12	600	635	80	46	9-13/16	7-3/16	7	A	
58R	10-5872	12	580	700	80	46	9-13/16	7-3/16	7	A	
59	10-5972	12	590	710	100	58	10-1/16	7-11/16	7-3/4	A	
65	10-6500	12	850	1000	160	93	11-9/16	7-7/16	7-9/16	A	
75	10-7584	12	700	910	100	58	9-7/16	7-1/16	7-3/16	S	
78	10-7870	12	770	950	120	70	10-3/16	6-13/16	7-3/16	S	
79	10-7972	12	880	1000	140	81	12-1/16	7-1/16	7-3/8	S	
85	10-8500	12	630	785	90	52	9	6-13/16	8	A	
86	10-8672	12	630	785	90	52	9	6-13/16	8	A	
90	10-9000	12	600	720	80	46	9-9/16	6-15/16	6-15/16	A	
91	10-9100	12	700	850	100	58	11	6-7/8	6-7/8	A	
93	10-9300	12	800	950	150	87	13-7/8	6-7/8	6-7/8	A	
94R/L4/H7	10-9400	12	730	875	140	80	12-7/16	6-15/16	7-1/2	A	
96R	10-9672	12	590	710	95	55	9-5/8	6-7/8	6-7/8	A	
100	10-1000	12	770	950	120	70	10-1/6	7-1/16	7-3/8	S	
101	10-1010	12	540	635	115	67	10-1/4	7-1/16	6-11/16	A	
121R	10-1210	12	550	660	90	52	8-1/8	6-7/8	7-3/4	A	
124R	10-1240	12	700	850	110	64	10-3/16	6-7/8	8-7/16	A	
151R	10-1510	12	340	410	55	36	7-1/3	5	8-7/8	A	
Certified (Flooded)											
75DT	10-3572	12	525	630	85	49	9	6-15/16	8-1/8	A,S	
78DT	10-3472	12	650	800	100	58	10-3/16	7-1/16	8-1/8	A,S	
65	10-6503	12	650	800	130	75	11-9/16	7-7/16	7-9/16	A	
75	10-7503	12	630	785	90	52	9-7/16	6-13/16	7-3/16	S	
Optima RED TOP (Starting AGM)											
34/78	10-0011	12	800	1000	100	50	10-1/16	6-15/16	7-7/8	A,S	
75/25	10-0012	12	720	910	90	44	9-3/8	6-13/16	7-3/4	A,S	
34R	10-0013	12	800	1000	100	50	10-1/16	6-7/8	7-7/8	A	
Optima YELLOW TOP (Dual Purpose AGM)											
34/78	10-0020	12	750	870	120	55	10-1/16	6-15/16	7-7/8	A,S	
35	10-0021	12	620	770	100	48	9-3/8	6-3/4	7-11/16	A	
51R	10-0022	12	450	575	66	38	9-5/16	5-1/6	8-15/16	A	

Product specifications are subject to change.



Dec-14