

Automotive Batteries										
BCI Group Size	Part Number	Volts	Cold Cranking Amps @ 0°F	Cranking Amps @ 32°F	Reserve Capacity Min @ 25A	Ah Capacity (20hr)	Length (in)	Width (in)	Height (in)	Battery Terminal Type
MotoMaster Eliminator Ultra XD (High Performance AGM)										
34/78DT	10-7850	12	880	1050	133	63	10 7/8	7	7 3/4	A,S
65	10-6550	12	930	1070	135	68	11 3/4	7 5/16	7 1/2	A
MotoMaster Eliminator Ultra (AGM)										
34R	10-2420	12	775	890	120	55	10 3/4	6 7/8	8	A
34	10-3420	12	775	890	120	55	10 3/4	6 7/8	8	A
35/85	10-3520	12	680	800	100	50	9-9/16	6 7/8	7 3/4	A
48 (H6/L3)	10-4820	12	760	875	120	70	11	6 7/8	7 1/2	A
49 (H8/L5)	10-4920	12	850	975	170	92	13 15/16	6 7/8	7 1/2	A
51R	10-5120	12	440	530	75	45	9 1/3	5	8 5/8	A
546B24R	10-5122	12	325	390	60	46	9 1/4	5	8 5/8	JIS
65	10-6520	12	750	860	150	75	12	7 3/8	7 5/8	A
78	10-7820	12	775	890	120	55	10 3/4	6 7/8	7 1/4	S
94R (H7/L4)	10-9420	12	800	920	140	80	12 7/16	6 7/8	7 1/2	A
MotoMaster Eliminator (Flooded)										
75/86DT	10-7580	12	690	850	95	--	9 3/4	7	8 1/8	A,S
34/78DT	10-7880	12	800	985	115	--	10 3/4	6 7/8	8	A,S
24F	10-2485	12	725	890	120	--	10 3/4	6 3/4	9	A
24	10-2486	12	725	890	120	--	10 3/4	6 3/4	9	A
26R	10-2685	12	540	665	80	--	8 3/4	6 3/4	8	A
34	10-3485	12	800	985	115	--	10 3/4	6 7/8	8	A
35	10-3585	12	640	785	95	--	9 3/4	6 7/8	8 7/8	A
40R (T6/LB3)	10-4085	12	650	800	105	50	11	6 7/8	6 7/8	A
47 (H5/L2)	10-4785	12	650	800	100	60	9 4/7	6 7/8	7 1/2	A
48 (H6/L3)	10-4885	12	730	900	120	72	11	6 7/8	7 1/2	A
49 (H8/L5)	10-4985	12	900	1105	185	100	14	6 7/8	7 1/2	A
51R	10-5185	12	500	615	75	--	9 3/8	5	8 3/4	A
51	10-5186	12	500	615	75	--	9 3/8	5	8 3/4	A
65	10-6585	12	750	925	140	--	12	7 3/8	7 5/8	A
75	10-7585	12	690	850	95	--	9 3/4	7	7 1/4	S
86	10-8685	12	690	850	90	--	9	6 7/8	8 1/8	A
94R (H7/L4)	10-9485	12	790	970	140	80	12 4/9	6 7/8	7 1/2	A
MotoMaster (Flooded)										
75/86DT	10-3570	12	650	800	90	--	9 3/4	7	8 1/8	A,S
34/78DT	10-3478	12	800	985	115	--	10 3/4	6 7/8	8	A,S
24F	10-2400	12	650	800	115	--	10 3/4	6 3/4	9	A
24	10-2470	12	650	800	115	--	10 3/4	6 3/4	9	A
25	10-2500	12	550	675	90	--	9 3/4	6 7/8	8 7/8	A
26	10-2600	12	540	665	80	--	8 3/4	6 3/4	8	A
26R	10-2673	12	510	625	70	--	8 3/4	6 3/4	8	A
27F	10-2700	12	710	875	120	--	12 3/8	6 3/4	9	A
27	10-2772	12	710	875	120	--	12	6 3/4	9	A
34	10-3400	12	690	850	110	--	10 3/4	6 7/8	8	A
35	10-3501	12	550	675	90	--	9 3/4	6 7/8	8 7/8	A
36R	10-3672	12	650	800	120	--	10 1/4	7 1/4	8	A
40R (T6/LB3)	10-4072	12	590	725	100	48	11	6 7/8	6 7/8	A
41	10-4100	12	650	800	100	--	11 9/16	6 7/8	6 7/8	A
42/58R	10-4200	12	500	615	75	--	10	7 1/4	6 7/8	A
46A24L	10-4672	12	320	400	45	--	7 3/4	5 1/8	7 1/4	A
47 (H5/L2)	10-4700	12	600	740	95	60	9 9/16	6 7/8	7 1/2	A
48 (H6/L3)	10-4800	12	680	835	120	70	11	6 7/8	7 1/2	A
49 (H8/L5)	10-4900	12	850	1035	170	95	13 15/16	6 7/8	7 1/2	A
51R	10-5100	12	450	555	70	--	9 3/8	5	8 3/4	A
51	10-5101	12	450	555	70	--	9 3/8	5	8 3/4	A
55	10-5672	12	540	665	75	--	8 3/4	6	8 1/2	A
58	10-5858	12	580	715	85	--	10	7 1/4	7	A
58R	10-5872	12	580	715	85	--	10	7 1/4	6 7/8	A
59	10-5972	12	590	725	100	--	9 1/2	7 4/9	7 1/2	A
65	10-6500	12	850	1045	150	--	12	7 3/8	7 5/8	A
75	10-7584	12	650	800	90	--	9 3/4	7	7 1/4	S
78	10-7870	12	800	985	115	--	10 3/4	6 7/8	7 1/4	S
79	10-7972	12	840	1035	140	--	12 1/16	7 1/16	7 3/8	S
85	10-8500	12	650	800	110	--	9	6 7/8	8 1/8	A
86	10-8672	12	640	785	90	--	9	6 7/8	8 1/8	A
90 (T5/LB2)	10-9000	12	600	740	90	45	9 6/16	6 7/8	6 7/8	A
91 (T6/LB3)	10-9100	12	700	860	100	50	11	6 7/8	6 7/8	A
93 (T8/LB5)	10-9300	12	800	985	130	65	13 15/16	6 7/8	6 7/8	A
94R (H7/L4)	10-9400	12	730	895	120	78	12 7/16	6 7/8	7 1/2	A
96R	10-9672	12	600	740	90	45	9 9/16	6 7/8	6 7/8	A
101	10-1010	12	650	800	110	--	10 1/4	7 1/16	6 11/16	A
121R	10-1210	12	550	675	80	--	8 1/4	7	8 1/8	A
124R	10-1240	12	700	860	100	--	10 1/4	6 7/8	8 3/8	A
151R	10-1510	12	360	470	60	--	7 1/4	5	8 3/4	A
Certified (Flooded)										
75/86DT	10-3572	12	540	665	85	--	9 3/4	7	8 1/8	A,S
34/78DT	10-3472	12	690	850	110	--	10 3/4	6 7/8	8	A,S
65	10-6503	12	675	830	130	--	12	7 3/8	7 5/8	A
75	10-7503	12	540	665	85	--	9 3/4	7	7 1/4	S
Optima RED TOP (Starting AGM)										
34/78	10-0011	12	800	1000	100	50	10-1/16	6-15/16	7-7/8	A,S
75/25	10-0012	12	720	910	90	44	9-3/8	6-13/16	7-3/4	A,S
34R	10-0013	12	800	1000	100	50	10-1/16	6-7/8	7-7/8	A
Optima YELLOW TOP (Dual Purpose AGM)										
34/78	10-0020	12	750	870	120	55	10-1/16	6-15/16	7-7/8	A,S
35	10-0021	12	620	770	100	48	9-3/8	6-3/4	7-11/16	A
51R	10-0022	12	450	575	66	38	9-5/16	5-1/6	8-15/16	A

Product specifications are subject to change.



TYPE A



TYPE S



TYPE JIS

Dec-14