

  Marine/RV Flooded  											
BCI Group Size	Part Number	Brand	Volts	MCA @ 32°F	Reserve Capacity Min @ 25A	Ah Capacity (20 hr)	Length (in)	Width (in)	Height (in)	Weight (lbs)	Terminal Type
Starting											
24	010-2493	Nautilus	12	650	80	--	10-1/4	6-13/16	9-1/16	37.60	M (3/8P 5/16N)
24	010-2495	Nautilus	12	1000	115	--	10-1/4	6-13/16	9-1/16	52.10	M (3/8P 5/16N)
Dual Purpose Starting & Deep Cycle											
24	010-2499	Nautilus	12	625	120	70	10-1/4	6-13/16	9-7/16	44.40	M (3/8P 5/16N)
27	010-2799	Nautilus	12	730	160	100	12	6-13/16	9-7/16	57.50	M (3/8P 5/16N)
Deep Cycle											
31	010-3199	Nautilus	12	900	205	115	13	6-13/16	9-7/8	63.30	M (3/8P 5/16N)
4D	010-3028	Nautilus	12	850	250	160	20-3/4	8-3/4	10-11/16	103.90	WNT2
8D	010-3029	Nautilus	12	1200	400	200	20-3/4	11	10-11/16	138.60	WNT2
GC2	010-2000	MotoMaster	6	--	480	226	7-1/8	10-7/8	66.30	--	LP1
GC2	010-2010	Exide	6	--	390	186	7-1/8	10-7/8	61.50	--	LP1

Marine/RV AGM (Absorbed Glass Mat)											
BCI Group Size	Part Number	Brand	Volts	MCA @ 32°F	Reserve Capacity Min @ 25A	Ah Capacity (20 hr)	Length (in)	Width (in)	Height (in)	Weight (lbs)	Terminal Type
Premium AGM											
24	010-2498	Nautilus Ultra	12	930	130	75	10-1/4	6-13/16	9-7/16	53.00	M (3/8P 5/16N)
31	010-3190	Nautilus Ultra	12	1110	200	100	13	6-5/8	9-7/16	73.20	M (3/8P 5/16N)
High Performance Pure Lead AGM											
24	010-2496	Nautilus Ultra XD	12	1000	160	76	10-7/8	6-3/4	8-3/4	59.50	M (3/8)
27	010-2796	Nautilus Ultra XD	12	1110	190	88	12-7/16	6-3/4	8-3/4	70.30	M (3/8)
31	010-3196	Nautilus Ultra XD	12	1370	220	100	13	6-3/4	9-1/4	76.20	M (3/8)

Product specifications are subject to change.



Jun-14