







This reel has been made by craftsmer using the best materials available to ensure its reliability Its high quality components are precision machined with the absolute minimum susceptibility to wear or the need for future readjustment.

Given care and periodic cleaning eyour reel will be a faithful servant and give you years of superb performance.

Hardy & Greys Limited, Willowburn, Alnwick, Northumberland: NE66 2PF, England Tel 744 (0)1665 602771 Fax +44 (0)1665 602389 www.hardyfishing.com/_sales@hardyfishing.com

Care and maintenance

The same method of cleaning is valid for all reels in the Hardy Zane Aluminium series. This real has been designed to be used in fresh or saltwater, but when using in saltwater, extra care should be taken with the maintenance program.

- 1. Remove line and backing.
- 2. Remove the spool.
- 3. Flush away dirt by placing the spool and frame under a stream of warm fresh water.
- 4. Dry carefully with a lint free cloth
- 5. Lubricate with good quality oil at the points illustrated on the diagrams.
- 6. Always ensure the spool shaft is adequately greased.
- 7. Always turn the drag to the minimum setting to avoid compression of the pad.
- 8. Always ensure the reel and line are dry before storing in the case or pouch.
- 9. Oil the base of the handle (28).
- 10. Grease threads on drawbar (24) and ball channel on rear of central carrier (2).
- 11. Grease dog springs on cage inner (36).
- 12. Oil plungers on spool (10).
- 13. Remove spool cap, grease disc spring assembly.

*Refer to exploded diagram on reverse

Lifetime original user warranty

All Hardy Zane reels carry an original owner lifetime warranty against any defect in workmanship or materials. Should there be any defect, Hardy & Greys Ltd. will, at its option, repair or replace the item. This warranty does not cover damage caused by misuse, lack of maintenance, negligence or normal wear and tear. Warranty claims with the proof of purchase should be sent to:

Customer Service Department Hardy & Grevs Limited Willowburn Alnwick Northumberland NE66 2PF England


Tel +44 (0)1665 602771 Fax +44 (0)1665 602389

www.hardyfishing.com sales@hardyfishing.com All Zane Aluminium reels are pre-set in the factory to be left hand wind.

To change from left to right hand wind.


- 1. Using a coin or screwdriver, remove the lock screw (27) at the rear of the wheel. (The arrow on the screw indicates a clockwise direction to remove).
- 2. Unscrew regulator button (7).
- 3. Remove spool (15) from frame (1).
- 4. Remove clutch body assembly (9) from the frame.
- 5. Move the dogs (14) to a neutral position.
- 6. Tease the spring (36) off by the base closest to the Aluminium body. A small screwdriver or pin aids in this operation.
- 7. Place spring onto the opposite peg.
- 8. Repeat steps 6 and 7 on the opposite dog.
- 9. Replace clutch and gently twist into position to engage dogs.
- 10. Replace drum.
- 11. Replace regulator button.
- 12. Replace the stop screw.
- 13. Your Zane Aluminium reel is now in right hand wind.

Steps 1 and 2






Step 4



Assembly

Steps 3 and 4



Dogs in Left HW

Dogs in Neutral

Dogs in Right HW