

# LEVOLOR®

## Custom Shutters

French Door Cut-Out Template

Place edge against  
baseplate of handle.

1

Align this line with center of  
baseplate or center line between  
handle and deadbolt.

2

3

Check handle clearance  
by rotating door handle.  
Handle must rotate  
within this arc.

(see back for additional details)

This line indicates the hidden  
edge of the frame.

Confirm fit and placement of  
frame next to molding and #1  
alignment with baseplate.

4

Cut here for placement.



### French Door Cut-Out Specifications

Louver Size	2 1/2 inch	3 1/2 inch	4 1/2 inch
Minimum Width:	18"	18"	18"
Maximum Width:	36"	36"	36"
Minimum Height:	36"	38"	40"
Maximum Height:	96"	96"	96"
Maximum Square Feet:	15	15	15
Minimum Cut-Out Height	17 3/4"	18 3/4"	19 3/4"

### Outside Mount Depth Clearance (Extensions Required)

L Frame (no molding around glass)	2 1/2 inch	3 1/2 inch	4 1/2 inch
Tilt Bar	0	1	2
Gear Closure System	0	1	2
Motorization	0	1	2

L Frame (with molding around glass)	2 1/2 inch	3 1/2 inch	4 1/2 inch
Tilt Bar	1	2	3
Gear Closure System	1	2	3
Motorization	1	2	3

### Features & Benefits

- Available with 4-sided L Frame only
- Available in all louver sizes
- Increased cut-out size to allow for larger handles and deadbolts
- Plate integrated into shutter frame
- Divider rail available (centered on cutout body)



Cut here for placement.

