

# LEVOLOR®

## Custom Shutters

French Door Cut-Out Template

Cut here for placement.

Place edge against  
baseplate of handle.

1

Align/Tape Here

Align/Tape Here

2

Align this line with center of baseplate or centerline between handle and deadbolt.

3

Check handle clearance by rotating door handle. Handle must rotate within this arc.

(See page 3 for additional details)

Cut here for placement.

This line indicates the hidden edge of the frame.

Confirm fit and placement of frame next to molding and #1 alignment with baseplate.

4

## French Door Cut-Out Specifications

	2 ½ inch	3 ½ inch	4 ½ inch
Minimum Width:	18"	18"	18"
Maximum Width:	36"	36"	36"
Minimum Height:	36"	38"	40"
Maximum Height:	96"	96"	96"
Maximum Square Feet:	15	15	15
Minimum Cut-Out Height	17 ¾"	18 ¾"	19 ¾"

## OM Depth Clearance (Extensions Required)

L Frame (no molding around glass)	2 ½ inch	3 ½ inch	4 ½ inch
Tilt Bar	0	1	2
Clear Tilt	1	2	3
Gear System	0	1	2

L Frame (with molding around glass)	2 ½ inch	3 ½ inch	4 ½ inch
Tilt Bar	1	2	3
Clear Tilt	2	3	4
Gear System	1	2	3

## Features & Benefits

- Available with 4-sided L Frame only
- Available in all louver sizes
- Increased cut-out size to allow for larger handles and deadbolts
- Plate integrated into shutter frame
- Divider rail available (centered on cut-out body)