



POWER & EFFICIENCY			
INPUT POWER OPTIONS	AC 1PH 200-240V 50/60Hz   AC 3PH 200-240V 50/60Hz   AC 3PH 380-480V 50/60Hz		
CURRENT AT MAX SPEED (Amp)	4.5 - 3.9 A	2.4 - 2.1 A	2.0 - 1.6 A
POWER (hp)	5/8 HP		
MAXIMUM SPEED (RPM)	107 RPM		
MAX AFFECTED AREA	70 ft Dia   4,900 sqft		

DIMENSIONS & WEIGHT	
FAN DIAMETER	14 ft
FAN WEIGHT	128 lbs (58 kg)

The diagram shows a side profile of the fan. A horizontal line indicates the 14 ft diameter. A vertical line from the ceiling to the fan's mounting bracket is labeled '(A) MINIMUM 2 ft'. A detail of the mounting bracket shows a 5 INCH (127MM) dimension. The fan is shown with a downrod.

Pictured with 2 ft downrod

MOUNTING & SAFETY	
MOUNTING OPTIONS	I-beam   Glulam
DOWNROD (A)	Downrods available in 1 ft increments: 2 ft min., 10 ft max. <b>Downrod length must be specified at time of order.</b>
SAFETY FEATURES	Fan Retention System   Airfoil Retention System   Fire relay

IN THE BOX	
INCLUDED	Fan I-beam mount with pre-wired downrod   Control panel   Install manual Wall Control   Mounting hardware kit   Communication Kit   Guy wire kit
OPTIONAL	Additional cable lengths   Network Controller   Glulam brackets

WARRANTY & CERTIFICATIONS	
CERTIFICATIONS	ETL/Intertek-certified to ANSI/UL 507 and CSA C22.2 No. 113 in North America
WARRANTY <sup>1</sup>	10-year, Non-Prorated Warranty