



POWER & EFFICIENCY

| | | | |
|----------------------------|---|-------------|-------------|
| INPUT POWER OPTIONS | AC 1PH 200-240V 50/60Hz AC 3PH 200-240V 50/60Hz AC 3PH 380-480V 50/60Hz | | |
| CURRENT AT MAX SPEED (Amp) | 5.6 - 4.7 A | 2.8 - 2.4 A | 2.2 - 1.9 A |
| POWER (hp) | 5/8 HP | | |
| MAXIMUM SPEED (RPM) | 95 RPM | | |
| MAX AFFECTED AREA | 80 ft Dia 6,400 sqft | | |

DIMENSIONS & WEIGHT

| | |
|--------------|-----------------|
| FAN DIAMETER | 16 ft |
| FAN WEIGHT | 135 lbs (61 kg) |

Pictured with 2 ft downrod

MOUNTING & SAFETY

| | |
|------------------|---|
| MOUNTING OPTIONS | I-beam Glulam |
| DOWNROD (A) | Downrods available in 1 ft increments: 2 ft min., 10 ft max. Downrod length must be specified at time of order. |
| SAFETY FEATURES | Fan Retention System Airfoil Retention System Fire Relay |

IN THE BOX

| | |
|----------|---|
| INCLUDED | Fan I-beam mount with pre-wired downrod Control panel Install manual Wall control Mounting hardware kit Communication kit Guy wire kit |
| OPTIONAL | Additional cable lengths Network Controller Glulam brackets |

WARRANTY & CERTIFICATIONS

| | |
|-----------------------|--|
| CERTIFICATIONS | ETL/Intertek-certified to ANSI/UL 507 and CSA C22.2 No. 113 in North America |
| WARRANTY ¹ | 10-year, Non-Prorated Warranty |

¹See complete warranty for details.